ICEN Industrial Portable Air Conditioners

The ICEN Industrial Portable Air Conditioner comes in 3 different models allowing for multiple uses and applications in the commercial and industrial markets. The ICEN range offers an effective cooling solution for a variety of applications with features such as spot cooling for large areas where cooling of the entire area is not practical. A dedicated spot cooling thermostat controls the unit in this application. These air conditioners can also be used in smaller areas of up to 100m² for room cooling.

A control panel provides ease of use and contains a self-diagnostic function and display, showing operating modes, room and set temperatures, and faults. If an abnormal operation occurs, a visual display of the fault is shown. Lockable wheels are included for easy portability.



Uses	Applications Features		
Room Cooling	Warehouses, Workshops & Factories	ories Easy Installation	
Spot Cooling	Commerical Kitchens	Cleanse & dehumidfies the air	
Temporary Cooling	Hospitals & Laboratories	Washable filters	
	Emergency Cooling & Server Rooms	Self-diagnostic system	
	Multiworkstations	Auto-Restart (power interruption)	
	Marquee events	Compressor time delay	
	Temporary office cooling	Anti-freezing device	
	Equipment spot cooling		
	Military use - tents, aircraft hangars		





ICEN Industrial Portable Air Conditioners

TECHNICAL DATA SHEET

SPECIFICATION				
Model No	IPAC-47	IPAC-61	IPAC-94	
Cooling Capacity KW BTU	4.7 16,000	6.1 21,000	9.4 32,000	
Air Flow (L/s)	189/222	219/264	366/416	
Power Consumption	1.7KW	2.1KW	3.3KW	
Voltage	220~240V / 50Hz	220~240V / 50Hz	220~240V / 50Hz	
Current (A)	7.5	9.5	16.5	
Plug Connection	3 pin 10amp	3 pin 10amp	Fixed wiring*	
Refrigerant	R32	R32	R32	
Refrigerant Charge	950 grams (+/-10g)	1050 grams (+/-10g)	1500 grams (+/-10g)	
EER (Energy Effecient Ratio) BTU/Wh	9.8	-	10.6	
Cooling Area (m2) (room mode)	40	50	100	
No. of Cool Air Duct	2	2	3	
Fan Speed	2	2	2	
Weight	86kg	88kg	110kg	
Dimensions (mm)	(W)523x(D)671x(H)1042	(W)523x(D)671x(H)1042	(W)660x(D)885x(H)1380	
Country of Manufacture	South Korea	South Korea	South Korea	
Cable Length	3m	3m	3m	

^{*} Fixed wiring - a qualified electrician is required to do any fixed wiring work for this appliance



